



TT3509

PATENT

- 1 -

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application: Boswell et al.
Serial No.: 09/619,037
Filed: July 19, 2000
Art Unit: 2182
Examiner: T. R. Payton
For: SYSTEM AND METHOD FOR PROTECTING AGAINST
UNAUTHORIZED USE OF SOFTWARE BY
AUTOMATICALLY RECEIVING PCI VENDOR ID FROM
VENDOR

DECLARATION UNDER 37 C.F.R. § 1.131 OF KELLY KORDZIK

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Dear Sir:

I, Kelly Kordzik, declare on the basis of personal knowledge as follows:

CERTIFICATION UNDER 37 C.F.R. § 1.8

I hereby certify that this correspondence is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to Mail Stop Amendment, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450, on 7-6, 2004.


Signature

Toni Stanley
(Printed name of person certifying)

1. I am the patent attorney who prepared the above identified patent application on behalf of the inventors and their assignee Advanced Micro Devices, Inc.

2. Exhibit A attached hereto is a printed copy of an e-mail from me to Tim Maleck, one of the inventors of the above-identified patent application on June 28, 2000. Exhibit A demonstrates that I was intending to transmit a facsimile of the above-identified patent application draft to Mr. Maleck for his review and the review of his co-inventors.

3. Exhibit C is a copy of printouts of several e-mail exchanges between me and Mr. Tim Maleck on the dates of June 28-29, 2000. On one of the e-mail exchanges on June 28, 2000, Exhibit C shows that I informed Mr. Maleck that I was going to fax him the patent application draft referred to in Exhibit A on June 28, 2000.

4. Exhibit B is a copy of the fax transmission of the patent application draft from me to Tim Maleck on June 28, 2000, as indicated by the e-mail message in Exhibit C. The first page of Exhibit B shows that the facsimile transmission was successful. The remaining pages of Exhibit B show that the draft sent to Mr. Maleck on June 28, 2000 is virtually identical to the version of the patent application as filed.

5. Exhibit C also shows a printout of an e-mail message from Mr. Tim Maleck to me where he informs me that the patent application is ready to file.


6. Exhibit D is a copy of a letter on July 11, 2000 from my secretary, Toni Asendorf, to AMD enclosing the patent application and filing papers ready for execution by the inventors. This letter further states that upon successful execution of the filing papers, they were to be returned to Ms. Asendorf for filing in the PTO.

I hereby declare that all statements made herein of my knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and alike so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of

the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Respectfully submitted,

WINSTEAD SECHREST & MINICK P.C.
Attorneys for Applicant

By: 
Kelly K. Kordzik
Reg. No. 36,571


P.O. Box 50784
Dallas, Texas 75201
(512) 370-2851

Austin_1\2536861
184-P002US 7/2/2004

Kordzik, Kelly

EXHIBIT A

From: Kordzik, Kelly
Sent: Wednesday, June 28, 2000 6:13 PM
To: 'tim.maleck@amd.com'
Cc: beth.apperley@amd.com
Subject: Re: Points of clarification for PCI vendor identification based on CODEC ID:



Tim, thanks for your changes.


I will fax a revised version tomorrow. Please have your co-inventors review the final draft.

Thanks

Kelly K. Kordzik
Winstead Sechrest & Minick P.C.
100 Congress, Suite 800
Austin, Texas 78701
512.370.2851
Fax 512.370.2850
kkordzik@winstead.com
www.winstead.com

EXHIBIT B

Confirmation Report-Memory Send



Time : Jun-28-2000 06:32pm
Tel line 1 : 5123702855
Tel line 2 : 5124574206
Name : Winstead Sechrest & Minick P.C.

Job number : 467
Date : Jun-28 06:29pm
To : 2#196#96026582
Document Pages : 021
Start time : Jun-28 06:29pm
End time : Jun-28 06:32pm
Pages sent : 021
Status : OK

Job number : 467

*** SEND SUCCESSFUL ***

WINSTEAD SECHREST & MINICK
A Professional Corporation | Attorneys & Counselors

WSM

Suite 800
100 Congress Avenue
Austin, Texas 78701
512/474-4330
fax 512/370-2850

www.winstead.com

direct dial: (512) 370-2851
kkordzik@winstead.com

TELECOMMUNICATION TRANSMITTAL

PLEASE DELIVER TO THE FOLLOWING:	TELEPHONE NUMBER:	FAX NUMBER:
<u>Tim Maleck</u>		<u>602-6582</u>

FROM: KELLY K. KORDZIK

The information contained in this facsimile message is attorney privileged and confidential information intended for the use of the individual or entity named above. If the reader of this message is not the intended recipient, or the employee or agent responsible to deliver it to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this fax in error, please immediately notify us by telephone, and return the original message to us at the above address via the U. S. Postal Service.

DATE: 6/28/00 TIME IN: 6:30 pm

NUMBER OF PAGES: 21 INCLUDING COVER SHEET. PLEASE CALL THE FAX OPERATOR AT 512/370-2824 AS SOON AS POSSIBLE IF YOU DO NOT RECEIVE THE TOTAL NUMBER OF PAGES OR IF TRANSMISSION IS NOT LEGIBLE.

ATTORNEY #: 207 CLIENT-MATTER #: 184-P00245

ADDITIONAL MESSAGE: 2#196#

☒ ORIGINAL WILL NOT FOLLOW

☐ ORIGINAL WILL FOLLOW VIA:

☐ Regular Mail ☐ Hand Delivery
☐ Overnight Delivery ☐ Other

ODMA\PCDOCS\AUSTIN_1\142912\1
207:999993-1

TT3509

SYSTEM AND METHOD FOR PROTECTING AGAINST
UNAUTHORIZED USE OF SOFTWARE BY AUTOMATICALLY
RECEIVING PCI VENDOR ID FROM VENDOR

CROSS-REFERENCE TO RELATED APPLICATION

The present application is related to U.S. Patent Application Serial No. 09/498,156 (Attorney Docket No. TT3806), entitled "Virtual Rom For Device Enumeration," which is hereby incorporated by reference herein.

TECHNICAL FIELD

The present invention relates in general to data processing systems, and in particular, to peripheral devices used within such data processing systems.

5

BACKGROUND INFORMATION

Modems are now a required component in a Windows-based personal computer ("PC") according to Microsoft's PC99 specification. Given the increase in

processing speed in PC's, the modem function is being largely implemented in software running on the PC processor under the Windows operating system. This is done in order to continue reducing the cost of the modem component and to provide increased flexibility of software upgrades.

5 The architecture of the software consists of driver software and a minimal hardware set. The hardware provides an interface to the host computer memory and to the analog phone line. An industry standard has been provided that defines the interface between the driver software and the hardware for soft modems. This standard is the Intel AC97 specification. This specifies a common hardware interface
10 to any soft modem drivers. Given that the PC architecture is standardized and now the modem hardware is standardized, all that remains proprietary is the actual modem software. The bulk of the intellectual property for the soft modem is contained in the soft modem driver. Given that modems are required equipment for PC99 compliant PC's, and the modem is now essentially software, there is a risk of piracy for the
15 vendors of the soft modem intellectual property. A typical business model for the soft modem company is based on royalties per copy. The problem is how to track the proliferation of copies of the soft modem drivers to account for royalty disbursements.

20 Therefore, what is needed in the art is a solution for how to track the number of PC's that are utilizing a soft modem functionality. As a result, there is a need for a

TT3509

technique for authentication before the driver software will perform the soft modem function on a given codec (coder/decoder).

SUMMARY OF THE INVENTION

5 The present invention addresses the foregoing need by providing a process for identifying a soft modem interface for an identification code and then setting a vendor ID in the computer PCI configuration space. This happens during the BIOS plug and play ("PnP") enumeration process, before the operating system becomes available. The authentication block performs two functions that enable it to authenticate a codec. The first step is a codec query protocol that reads a hidden ID from an unpublished register within the codec. The second half of the process is to use the
10 characteristics of the device itself as a means of identification.

The foregoing has outlined rather broadly the features and technical advantages of the present invention in order that the detailed description of the invention that follows may be better understood. Additional features and advantages of the invention will be described hereinafter which form the subject of the claims of
15 the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention, and the advantages thereof, reference is now made to the following descriptions taken in conjunction with the accompanying drawings, in which:

FIGURE 1 illustrates an embodiment of the present invention;

FIGURE 2 illustrates a flow diagram in accordance with the present invention; and

FIGURE 3 illustrates a data processing system configured in accordance with the present invention.

DETAILED DESCRIPTION

5 In the following description, numerous specific details are set forth such as specific peripheral devices, etc. to provide a thorough understanding of the present invention. However, it will be obvious to those skilled in the art that the present invention may be practiced without such specific details. In other instances, well-known circuits have been shown in block diagram form in order not to obscure the present invention in unnecessary detail. For the most part, details concerning timing considerations and the like have been omitted in as much as such details are
10 not necessary to obtain a complete understanding of the present invention and are within the skills of persons of ordinary skill in the relevant art.

Refer now to the drawings wherein depicted elements are not necessarily shown to scale and wherein like or similar elements are designated by the same reference numeral through the several views.

15 The present invention is implemented with respect to use of a data processing system, and a PCI (Peripheral Component Interconnect) bus technology. Since there are many references regarding the PCI bus and its implementation of plug-n-play (PnP) capabilities, no further discussion is provided. Furthermore, the present invention pertains to enumeration of peripheral devices, which is discussed in the
20 cross-reference related application previously incorporated by reference.

Referring to FIGURE 3, there is illustrated a PC operating system and hardware 313 configured in accordance with the present invention having central processing unit (CPU) 310, such as a conventional microprocessor, and a number of other units interconnected via system bus 312. Data processing system 313 includes random access memory (RAM) 314, read only memory (ROM) 316, and input/output (I/O) adapter 318 for connecting peripheral devices such as disk units 320 and tape drives 340 to bus 312, user interface adapter 322 for connecting keyboard 324, mouse 326, and/or other user interface devices such as a touch screen device (not shown) to bus 312, communication adapter 334 for connecting data processing system 313 to a data processing network, and display adapter 336 for connecting bus 312 to display device 338. CPU 310 may include other circuitry not shown herein, which will include circuitry commonly found within a microprocessor, e.g., execution unit, bus interface unit, arithmetic logic unit, etc. CPU 310 may also reside on a single integrated circuit.

Coupled to system 313 via a PCI bus 103 is PCI board 100, which includes a PCI controller with V.90 lift logic 102 and one or more vendor specific codecs 104 coupled to the controller 102 and to an RJ11 connector 105, as illustrated in FIGURE 1. The soft modem application/driver 101 runs on top of the operating system 313.

Referring to FIGURES 1 and 2, the system 313 is powered on in step 201. Next, in step 202, an initial codec query procedure is implemented whereby a state machine, which is implemented within the controller 102, will query the codec 104

for its unique identifier code (product ID) using AC97 transactions. This unique identifier code is in an addressable register 106 within the codec 104. This product ID code is the vendor specific ID appointed to the codec manufacturer by the PCI committee, which is an industry consortium that assigns numbers so that a driver or
5 operating system can read this vendor specific product ID for identifying the codec's manufacturer.

Thereafter in step 203, this product ID code is then placed in a temporary buffer within controller 102. It should be noted the controller 102 could be a stand alone PCI device or a PCI controller integrated into other core logic devices.

10 There are several possible mechanisms besides a state machine within controller 102 that may be implemented to read the product code 106. One alternative is to embed a small program within a ROM on the codec 104, which will include some executable code to read the product ID code 106 into a buffer in controller 102.

15 In step 204, the product ID code is then compared to a table of such codes to determine the `VENDOR_ID` needed for configuring the codec 104. An address register that is used by the AC97 controller 102 is set with the location of the configuration address space for the `VENDOR_ID`. The state machine will then copy the `VENDOR_ID` into this address register, which will be used later for enumeration
20 of the codec 104.

Thereafter, in step 205, the BIOS will enumerate the PCI bus and build a table for later use by the Windows operating system. The table will identify required drivers by the `VENDOR_ID` for each PCI device 104. This is the standard PCI enumeration cycle, whereby the `VENDOR_ID` is used to select a modem driver 101 created specifically for the codec 104. If the driver cannot be found, a dialog box can be programmed to pop up and ask the user for the specific driver software. In this way, a vendor of driver software can be ensured that, a driver cannot simply be copied without also needing the hardware (codec) needed by the driver 101.

The present invention is distinct from the prior art in that the prior art hard codes the `VENDOR_ID`'s as part of the manufacturing process of the PCI bus.

The effect of the present invention is to authenticate a vendor specific codec before the soft modem driver will provide the modem function to the PC. This ensures that copies of the soft modem driver can be tied to the sales of vendor specific codecs, thereby providing a hindrance to software piracy. This system also allows system manufacturers to use multiple software/codec vendors by providing the required configuration information to the system in a transparent manner. This simplifies the design process, lowering costs and complexity to the original equipment manufacturers and designers.

Although the present invention and its advantages have been described in detail, it should be understood that various changes, substitutions and alterations can

TT3509

be made herein without departing from the spirit and scope of the invention as defined by the appended claims.

WHAT IS CLAIMED IS:

- 1 1. A method comprising the steps of:
2 reading an identification code from a memory location on a codec, the
3 identification code unique to a manufacturer of the codec; and
4 loading a driver as a function of the identification code.
- 1 2. The method as recited in claim 1, wherein the driver is loaded only if the
2 unique identification code is read from the codec.
- 1 3. The method as recited in claim 2, wherein the loading step further comprises
2 the step of:
3 comparing the identification code to a list of codes having drivers associated
4 therewith.
- 1 4. The method as recited in claim 1, wherein the driver is supplied by the
2 manufacturer.
- 1 5. The method as recited in claim 1, wherein the identification code is assigned
2 by an industry standards organization.

- 1 6. The method as recited in claim 2, wherein the loading step is conducted as
- 2 part of a PCI enumeration process.

1 7. A PCI controller adaptable for coupling to a data processing system
2 comprising:

3 a codec query routine operable for reading an identification code from a
4 memory location on a codec, the identification code unique to a manufacturer of the
5 codec; and

6 a loader routine operable for loading a driver as a function of the identification
7 code, wherein the driver is loaded only if the unique identification code is read from
8 the codec.

1 8. The PCI controller as recited in claim 7, wherein the loader further compares
2 the identification code to a list of codes having drivers associated therewith.

1 9. The PCI controller as recited in claim 7, wherein the driver is supplied by the
2 manufacturer.

1 10. The PCI controller as recited in claim 9, wherein the identification code is
2 assigned by an industry standards organization.

1 11. The PCI controller as recited in claim 7, wherein the loading is conducted as
2 part of a PCI enumeration process.

3 12. A data processing system comprising:

4 a processor;
5 a memory device coupled to the processor by a local bus;
6 an input device coupled to the processor by the local bus;
7 an output device coupled to the processor by the local bus;
8 an operating system operable for running on the system;
9 a driver stored in the memory device;
10 a PCI bus coupled to the local bus;
11 a controller coupled to the PCI bus;
12 a codec coupled to the controller; and
13 a connector coupled to the codec and adaptable for coupling to a
14 telecommunications network, wherein the PCI controller further comprises:
15 a codec query routine operable for reading an identification code from
16 a memory location on a codec, the identification code unique to a manufacturer of the
17 codec; and
18 a loader routine operable for loading a driver as a function of the
19 identification code, wherein the driver is loaded only if the unique identification code
20 is read from the codec.

1 13. The data processing system as recited in claim 12, wherein the loader further
2 compares the identification code to a list of codes having drivers associated therewith.

1 14. The data processing system as recited in claim 12, wherein the driver is
2 supplied by the manufacturer.

1 15. The data processing system as recited in claim 13, wherein the identification
2 code is assigned by an industry standards organization.

1 16. The data processing system as recited in claim 12, wherein the loading is
2 conducted as part of a PCI enumeration process.

1 17. A controller comprising:
2 means for reading an identification code from a memory location on a codec,
3 the identification code unique to a manufacturer of the codec; and
4 means for loading a driver as a function of the identification code.

1 18. The controller as recited in claim 17, wherein the loading means further
2 comprises means for loading the driver only if the unique identification code is read
3 from the codec.

1 19. The controller as recited in claim 18, wherein the loading means further
2 comprises:
3 means for comparing the identification code to a list of codes having drivers
4 associated therewith.

1 20. The controller as recited in claim 19, wherein the driver is supplied by the
2 manufacturer.

1 21. The controller as recited in claim 20, wherein the identification code is
2 assigned by an industry standards organization.


SYSTEM AND METHOD FOR PROTECTING AGAINST UNAUTHORIZED USE
OF SOFTWARE BY AUTOMATICALLY RECEIVING PCI VENDOR ID FROM
VENDOR

5

ABSTRACT OF THE DISCLOSURE

At system power on, a query is sent from a PCI or host-based controller to an
attached codec for the vendor specific identification code associated with that codec.
10 The PCI/host controller then sets its PCI vendor and subvendor ID's to match the
specific system comprised of the controller and codec devices. That vendor specific
identification code is then utilized within the PCI enumeration process to search for
the specific modem driver associated with that codec.

2014-01-14 14:18:38



Points of clarification for PCI vendor identification based on CODEC ID:

PCI PnP uses a standard 16 DWORD configuration space

There is an option 48 DWORD space allocated in memory directly following the 16 DWORD vendor and device ID space.

This 64 DWORD device configuration table is contained in the device controller.

The pointer is a state machine that redirects the BIOS/Operating System PCI device query to the appropriate device/vendor ID table.

The BIOS/OS reads this table as it would any other PCI device. This requires no additional algorithms or changes to the system. It does not require any exotic BIOS snooping routines, unlike other automatic ID schemes.





FIG. 2







FIG. 3



Kordzik, Kelly

EXHIBIT C

From: tim.maleck@amd.com
Sent: Thursday, June 29, 2000 2:23 PM
To: KKordzik@winstead.com
Cc: beth.apperley@amd.com
Subject: RE: Points of clarification for PCI vendor identification based on CODEC ID:



Kelly,

The changes look good to me, so
its ready to file.

Tim

> -----Original Message-----

> From: Kordzik, Kelly [SMTP:KKordzik@winstead.com]
> Sent: Wednesday, June 28, 2000 6:22 PM
> To: Maleck, Tim
> Subject: RE: Points of clarification for PCI vendor identification
> based on CODEC ID:

> Actually, I will fax it tonight to 602-6582

> Kelly K. Kordzik
> Winstead Sechrest & Minick P.C.
> 100 Congress, Suite 800
> Austin, Texas 78701
> 512.370.2851
> Fax 512.370.2850

> kkordzik@winstead.com <mailto:kkordzik@winstead.com>
> www.winstead.com <http://www.winstead.com>

> INFORMATION CONTAINED IN THIS TRANSMISSION IS ATTORNEY-CLIENT PRIVILEGED
> AND
> CONFIDENTIAL. IT IS INTENDED FOR THE USE OF THE INDIVIDUAL OR ENTITY
> NAMED
> ABOVE. IF THE READER OF THIS MESSAGE IS NOT THE INTENDED RECIPIENT, YOU
> ARE
> HEREBY NOTIFIED THAT ANY DISSEMINATION, DISTRIBUTION OR COPY OF THIS
> COMMUNICATION IS STRICTLY PROHIBITED. IF YOU HAVE RECEIVED THIS
> COMMUNICATION IN ERROR, PLEASE IMMEDIATELY NOTIFY US BY TELEPHONE. THANK
> YOU.


> -----Original Message-----

> From: tim.maleck@amd.com [mailto:tim.maleck@amd.com]
> Sent: Wednesday, June 28, 2000 4:01 PM
> To: KKordzik@winstead.com
> Cc: beth.apperley@amd.com
> Subject: RE: Points of clarification for PCI vendor
> identification based on CODEC ID:

WINSTEAD SECHREST & MINICK

WSM

A Professional Corporation | Attorneys & Counselors



July 11, 2000

Suite 800
100 Congress Avenue
Austin, Texas 78701
512/474-4330
fax 512/370-2850
www.winstead.com

direct dial: 512-370-2828
tasendorf@winstead.com

VIA HAND DELIVERY

Ms. Kat Fenton
AMD
Technology Law Department
5204 E. Ben White Blvd.
Austin, Texas 78741


Re: AMD Docket No. TT3509
Our File No. 184-P002US

Dear Kat:

Enclosed please find the above identified patent application and filing papers ready for execution by the inventors. After the documents have been executed, please return them to my attention so we can file them with the PTO.

If you have any questions regarding this, please do not hesitate to give me a call.

Very truly yours,


Toni L. Asendorf
IP Secretary

/tla
Enclosures